



Schedule		Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage	Efficiency	Distribution
Symbol	Description														
□	A	4	Lithonia Lighting	DSX2 LED P3 40K TSW MVOLT	DSX2 LED P3 40K TSW MVOLT	LED	1	DSX2_LED_P3_40K_TSW_MVOLT_LT.res	29142	0.9	217	100%	TYPE VS, SHORT, RATED: B3 - UO - G3		
□	B2-EX	5	Lithonia Lighting	DSX2 LED P8 40K TFM MVOLT PER HS	DSX2 LED P8 40K TFM MVOLT with houseside shield	LED	1	DSX2_LED_P8_40K_TFM_MVOLT_LT_HS.res	38401	0.9	862	100%	TYPE III, SHORT, RATED: B3 - UO - G3		
□			Lithonia Lighting	DSX2 LED P8 40K TFM MVOLT PER HS	DSX2 LED P8 40K TFM MVOLT with houseside shield	LED	1	DSX2_LED_P8_40K_TFM_MVOLT_LT_HS.res	38401	0.9	431	100%	TYPE III, SHORT, RATED: B3 - UO - G3		
□			Lithonia Lighting	DSX2 LED P8 40K TFM MVOLT PER HS	DSX2 LED P8 40K TFM MVOLT with houseside shield	LED	1	DSX2_LED_P8_40K_TFM_MVOLT_LT_HS.res	38401	0.9	431	100%	TYPE III, SHORT, RATED: B3 - UO - G3		
□	C-EX	3	Lithonia Lighting	DSX2 LED P2 40K BLC MVOLT	DSX2 LED P2 40K BLC MVOLT	LED	1	DSX2_LED_P2_40K_BLC_MVOLT_LT.res	19720	0.9	185	100%	TYPE III, SHORT, RATED: B3 - UO - G3		
□	B-EX	4	Lithonia Lighting	DSX2 LED P8 40K TFM MVOLT PER HS	DSX2 LED P8 40K TFM MVOLT with houseside shield	LED	1	DSX2_LED_P8_40K_TFM_MVOLT_LT_HS.res	38401	0.9	431	100%	TYPE III, VERY SHORT, RATED: B3 - UO - G3		

### Statistics

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Calc Zone #1	+	0.9 fc	10.9 fc	0.0 fc	N/A	N/A
Central Building Lot	✗	1.6 fc	6.4 fc	0.0 fc	N/A	N/A
North Entry Road	✗	1.2 fc	4.8 fc	0.0 fc	N/A	N/A
North Parking Lot	✗	1.0 fc	10.9 fc	0.0 fc	N/A	N/A
PROPERTY LINE	+	0.0 fc	0.1 fc	0.0 fc	N/A	N/A
South Building Lot	✗	1.0 fc	3.5 fc	0.0 fc	N/A	N/A